PASSION FOR SPORTS GROUNDS





SMG Sportplatzmaschinenbau GmbH | Robert-Bosch-Str. 3, DE - 89269 Vöhringen / Germany | Phone: +49 (0) 7306 96 65 0
Fax: +49 (0) 7306 96 65 50 | info@smg-machines.com | www.smg-machines.com


WashMatic WM1200

WASHMATIC - REDEVELOPMENT



Tractor device for cleaning of synthetic sports surfaces by high pressure water.

The WashMatic WM1200 is a powerful front-mounted device for cleaning synthetic sports surfaces using high-pressure water. The unit is based on the proven technology of the previous WashMatic WM800 and has been developed for direct attachment to common municipal vehicles and tractors.



The WashMatic WM1200 utilizes the patented high-pressure technology of the WashMatic WM800. Eight diagonally arranged, rotating high-pressure nozzles clean the surface gently and effectively with an adjustable spray pressure of up to 170 bar. The applied water loosens dirt, organic residues as well as granulate and fiber abrasion (microplastic) from the surface. The water and released particles are then turbine-like vacuumed off by rapidly rotating blades and conveyed to a wastewater pump.


The working width of 1.20 m is designed for cleaning one lane of a running track (typically about 1.10 m wide) and allows complete surface cleaning in a single pass. The water consumption is approximately 50 liters per minute and can generally be supplied by the sports facility’s water system. If the water supply is insufficient, an external fresh-water buffer tank with pump can optionally be used.

Continuous fresh-water supply and wastewater discharge ensure uninterrupted operation. In addition, the unit can be connected to the ClearMatic CM1800 wastewater treatment

system – a mobile unit for treatment, filtration, and sludge dewatering of wastewater generated during the cleaning of synthetic sports surfaces (Part No. 6233350).

WashMatic WM1200 / Detail views

WASHMATIC - REDEVELOPMENT




Precise

Pressure gauge and valve for spray pressure up to 140 bar.



Simple

Engage Lever to activate the unit.




Powerful

Integrated dirty water pump.


WashMatic WM1200 / Detail views

WASHMATIC - REDEVELOPMENT



Effective

3-point front mounting.



Patented

Patented high- pressure cleaning technology.



Transport

Compact dimensions for easy transport.

WashMatic WM1200 / Detail views

WASHMATIC - REDEVELOPMENT

Item number/s:	*6243905*
Required power	50-60 HP
Required PTO drive	1,000 rpm, 6-spline, 1 3/8", rotation direction L or R (viewed from the front of the PTO shaft)
Required 3-point hitch	Category 2
Cleaning pressure	up to 170 bar
Working width	1,200 mm
Performance	300 - 350 m²/h (depending on type of surface and contamination)
Weight	550 kg
Dimensions	L 1,750 x B 1,700 x H 900 mm

Subject to technical changes

PASSION FOR SPORTS GROUNDS

SMG Sportplatzmaschinenbau GmbH | Robert-Bosch-Str. 3, DE - 89269 Vöhringen / Germany | Phone: +49 (0) 7306 96 65 0
Fax: +49 (0) 7306 96 65 50 | info@smg-machines.com | www.smg-machines.com