PASSION FOR SPORTS GROUNDS






SMG Sportplatzmaschinenbau GmbH | Robert-Bosch-Str. 3, DE - 89269 Vöhringen / Germany | Phone: +49 (0) 7306 96 65 0
Fax: +49 (0) 7306 96 65 50 | info@smg-machines.com | www.smg-machines.com

Oscillating brush OS1700 / OS1700 PTO

OSCILLATING BRUSH - FILLING



Brushing attachment for filling material, intensive erecting and sweeping of artificial turf fibres.
Working width 1,700 mm.

The oscillating brush OS1700/OS1700 PTO attachment is designed to straighten up the fibre and brushes the infill material into the artificial turf system. The oscillating movement of the brush unit allows multi directional work. The SandMatic, which is equipped with the very same oscillating brush feature, has been used for this purpose for years; it enables work "against" and "with" the pile. 4 adjustment spindles are used to precisely adjust the working depth in accordance with the pile height. The OS1700/OS17OO PTO attachment provides fibre support by distributing the infill material homogeneously throughout the artificial turf surface.

The OS1700/OS17OO PTO attachment can be used with brushes of di□fferent hardness/sti□ffness to loosen the infill material or to decompact the artificial turf surface (e.g.: when sand is used). This attachment can also be used as a sweeping brush for the maintenance of the artificial turf surface just by switching off□ the oscillating movement of the brushes. The working width is 1,700 mm.



Oscillating brush OS1700 / OS1700 PTO / Detail views

OSCILLATING BRUSH - FILLING



oscillating brush OS1700/OS1700 PTO




Different hardness/stiffness brushes available for all kinds of requirements, easy to change.



with 3-point rear attachment system, hydraulic drive

Oscillating brush OS1700 / OS1700 PTO / Detail views

OSCILLATING BRUSH - FILLING



with 3-point rear attachment system, drive via PTO shaft

Oscillating brush OS1700 / OS1700 PTO / Detail views

OSCILLATING BRUSH - FILLING

Item number/s:	*6212168 / OS1700* *6211848 / OS1700 PTO*
Drive	OS1700: Hydraulically, flow rate minimum 30 litres at 100 bar/min OS1700 PTO: PTO adaptor, 540 rpm
Working width	approx. 1,700 mm
Weight	187 kg
Dimensions	L 1,700 x W 900 x H 800 mm
Shipping dimensions	L 2,000 x W 1,000 x H 900 mm

Subject to technical changes

PASSION FOR SPORTS GROUNDS

SMG Sportplatzmaschinenbau GmbH | Robert-Bosch-Str. 3, DE - 89269 Vöhringen / Germany | Phone: +49 (0) 7306 96 65 0
Fax: +49 (0) 7306 96 65 50 | info@smg-machines.com | www.smg-machines.com